



Presentation:

Gazette



Image:

Small

Français



1 of 1

[View Images](#)

(21) Int. PCT/CH00/00017  
Application  
Number:

(22) Int. 11 January 2000  
Filing Date: (11.01.2000)

**(30) Priority Data**

199 00 792.6 12 January DE  
1999  
(12.01.1999)

**(71) Applicant:**

**DISETRONIC  
LICENSING AG**  
Brunnmattstrasse 6,  
CH-3401 Burgdorf ; (CH).  
[CH/CH]. (*for all  
designated states except US*)

**(72) Inventors; and****(75) Inventors/Applicants:**

**KIRCHHOFER**, Fritz  
Wassermatt, CH-3454  
Sumiswald ; (CH) [CH/CH].  
**GURTNER**, Thomas  
Haperigweg 6, CH-3425  
Koppigen ; (CH) [CH/CH].

**(81) Designated States:**

AE, AL, AM, AT, AU, AZ,  
BA, BB, BG, BR, BY, CA,  
CH, CN, CU, CZ, DE, DK,  
EE, ES, FI, GB, GD, GE,  
GH, GM, HR, HU, ID, IL,  
IN, IS, JP, KE, KG, KP, KR,  
KZ, LC, LK, LR, LS, LT,  
LU, LV, MD, MG, MK,  
MN, MW, MX, NO, NZ,  
PL, PT, RO, RU, SD, SE,  
SG, SI, SK, SL, TJ, TM,  
TR, TT, UA, UG, US, UZ,  
VN, YU, ZA, ZW ; ARIPO  
patent ( GH, GM, KE, LS,  
MW, SD, SL, SZ, TZ, UG.

(51) International  
Patent  
Classification<sup>7</sup>:  
**A61M 5/315**

A1

(11) Int. **WO**  
Publication  
Number: **00/41753**

(43) Int. 20 July 2000  
Publication (20.07.2000)  
Date:

**(54) Title:**DEVICE FOR ADMINISTERING AN  
INJECTABLE PRODUCT

**(57) Abstract**

The invention relates to a device for administering a dose, comprising a housing with a reservoir, a piston that pushes out the product from the reservoir when its is displaced towards an outlet of said reservoir in the advance direction, a drive member (6), a driven member that is entrained by the drive member (6) when said drive member (6) is displaced in the advance direction and that pushes the piston in the advance direction and a dosing member (15) that can be rotated around the displacement axis (V) of the drive member (6) to regulate the administration of a dose of the product to be delivered. The drive member (6) and the dosing member (15) come to rest with at least one stop (14, 18), one of which is embodied on the drive member (6) and the other one is configured on the dosing member (15). At least one of said stops (14, 18) runs at least spirally around the displacement axis (V) of the drive member (6). The at least one spiral stop (18) has a progression with a constant slope (&agr;).

